Perform the Pre-ride Inspection (P. 39) at each scheduled maintenance period.

ITEMS	FREQUENCY	NOTE	CRF450R/RWE	Each race or about 2.5 hours	Every 3 races or about 7.5 hours	Every 6 races or about 15.0 hours	Every 9 races or about 22.5 hours	Every 12 races or about 30.0 hours
			CRF450RX	Each race or about 3.5 hours	Every 2 races or about 7.5 hours	Every 4 races or about 15.0 hours	Every 6 races or about 22.5 hours	Every 8 races or about 30.0 hours
Fuel Line		NOTE 6		_				®
Fuel Pump Filter		NOTE 6						ß
Throttle Operation								
Air Filter		NOTE 1		С				
Crankcase Breather								
Spark Plug								
Valve Clearance/Decom System	pressor	NOTE 4				п		
Engine Oil		NOTE 3, 5				ß		
Engine Oil Filter		NOTE 3				®		
Engine Idle Speed								

WE RECOMMEND THESE ITEMS BE SERVICED BY REFERRING TO THE OFFICIAL HONDA SERVICE MANUAL.

This maintenance schedule is based upon average riding condition. Machine subjected to severe use require more frequent servicing.

Maintenance Legend

- I : Inspect (clean, adjust, lubricate, or replace, if necessary)
- L : Lubricate
- **R** : Replace
- C : Clean

ITEMS	FREQUENCY	NOTE	CRF450R/RWE	Each race or about 2.5 hours	Every 3 races or about 7.5 hours	Every 6 races or about 15.0 hours	Every 12 races or about 30.0 hours
			CRF450RX	Each race or about 3.5 hours	Every 2 races or about 7.5 hours	Every 4 races or about 15.0 hours	Every 8 races or about 30.0 hours
Piston and Piston Rings						®	
Piston Pin						ß	
Radiator Coolant		NOTE 2		П			
Cooling System							
Drive Chain				I L	®		
Drive Chain Slider							
Drive Chain Roller				I			
Drive Sprocket							
Driven Sprocket				I			
Brake Fluid		NOTE 2					
Brake Pads Wear					_		
Brake System							

Maintenance Schedule

ITEMS	FREQUENCY	NOTE	CRF450R/RWE	Each race or about 2.5 hours	Every 3 races or about 7.5 hours	Every 6 races or about 15.0 hours		Every 12 races or about 30.0 hours
			CRF450RX	Each race or about 3.5 hours	Every 2 races or about 7.5 hours	Every 4 races or about 15.0 hours	Every 6 races or about 22.5 hours	Every 8 races or about 30.0 hours
Clutch Fluid		NOTE 2		_				
Clutch System		NOTE 5						
Control Cables				I L				
Exhaust Pipe/Muffler								
Suspension								
Swingarm/Shock Linkage								
Fork Oil		NOTE 3					®	
Nuts, Bolts, Fasteners								
Wheels/Tires								
Steering Head Bearings								
Side Stand		NOTE 7						

Notes: 1 : Clean after every moto for dusty riding condition.

- 2 : Replace every 2 years. Replacement requires mechanical skill.
- 3 : Replace after the first break-in ride.

- 4 : Inspect after the first break-in ride.
- 5 : Replace the engine oil, if the clutch discs and plates are replaced.
- 6 : Replace every year.
- 7 : Only RX type.